INDUSTRIAL COMPONENT DATA

HC-26S1N8AQ0DU 1623277 PHOENIX CONTACT Rear panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-26S1N8AQ0DU



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-26S1N8AQ0DU
Catalog number	1623277
Category	Circular connector, mounting (without cable)
Minimum order	10 Pcs
Document ID	EO-8E34B32A12
Generated	2026-11-19

Product Overview

Rear panel feed-through
Rear wall pass-through, straight, Screw lock, M27, number of poles: 26, contact type: Female, Axial O-ring, Central fixing, shielded: yes, protection index: IP67, in plugged state, cable diameter range: 2 mm ... 14.5 mm, number of poles: 26, connection type: Crimped connection, series: HC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1623277
Packing unit 1
GTIN 4055626273020
Custom tariff number 85366990
General
Note Order information: Order crimp contacts Ø 1 mm separately
Type of locking Screw locking
Direction of rotation of contact chamber numbering Standard
Coding N
Contact connection method Crimp connection
Type of contacts Socket

Number of positions 26
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Conductor entry 2 mm ... 14.5 mm
Pg housing screw connection none
Mounting type Central fixing
Ambient conditions
Ambient temperature -20 °C ... 125 °C
Degree of protection IP67, when plugged in
Specifications according to DIN EN 61984:2001
Installation height max. 2000 m
Nominal / operating voltage of power contacts 150 V
Rated surge voltage of power contacts 1.5 kV
Overvoltage category of power contacts II
Degree of pollution of power contacts 3
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.1272607xxeCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440102eCl@ss 8.027440102eCl@ss 9.027440103
ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002635ETIM 6.0EC002061
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC 13.239121413

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-26S1N8AQ0DU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.