INDUSTRIAL COMPONENT DATA

# FOC-FDX20-PP-LCD6-MM 1019710 PHOENIX CONTACT Splice box

**Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-FDX20-PP-LCD6-MM**




| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | FOC-FDX20-PP-LCD6-MM |
| Catalog number | 1019710 |
| Category | Patch panel fibre optic |
| Minimum order | 1 Pcs |
| Document ID | EO-AA0B81E395 |
| Generated | 2026-11-18 |

## Product Overview

Splice box
Distributor, construction: Module for rail mounting, protection index: IP20, material: Steel sheet, connection type: M20 cable glands, cable output: up and down, color: traffic gray A RAL 7042
Distributor, Design: DIN rail module, Protection class: IP20, Material: Metal, Connection type: Splicing, Cable outlet: top and bottom, Housing size: 1, Colour: grey

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1019710
Packing unit 1 pc
GTIN 4055626701042
Weight per Piece (excluding packing) 703.400 g
Custom tariff number 85367000
Country of origin DE (Germany)
Mechanical characteristics
Number of slots 6
Connection profile LC-Duplex
Fiber type GOF

Ferrule diameter 1.25 mm
Insertion/withdrawal cycles >= 500
Connection method Cable gland M20
External cable diameter 6 mm ... 12 mm
Cable outlet above and below
Type of cable For all common cable types
Color traffic grey A RAL 7042
Mounting type DIN rail mounting
Degree of protection IP20
Type Rail-mountable module
No. of cable outlets 2
Type of the screw connection M20 x 1.5
Type of note Order information:
Note In addition, shrink splice protection (Order No.: 1019676) or crimp splice protection (Order No.: 1019678) must be ordered separately.
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (assembly) 0 °C ... 50 °C
Degree of protection IP20 (according to IEC 60529)
Material data
Flammability rating according to UL 94 V0
Housing material Sheet steel
Housing surface material Powder-coated, gray
Ferrule material Zirconia ceramics
Housing width 40 mm
Depth 115 mm
Height 130 mm
Line characteristics
Type of cable For all common cable types
Cable type Fiberglass
Transmission medium FO
Number of fibers 12
Fiber GOF
Standards and Regulations
Resistance to UV radiation yes
Flammability rating according to UL 94 V0
Shock DIN EN 61300-2-9: 2015-09
Environmental Product Compliance...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-FDX20-PP-LCD6-MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.