INDUSTRIAL COMPONENT DATA

# FOC-FDX20-PP-LCD6-OSA-PT9 1083665 PHOENIX CONTACT DIN rail splice box, fully mounted ready to splice, for 6x..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-FDX20-PP-LCD6-OSA-PT9**




| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | FOC-FDX20-PP-LCD6-OSA-PT9 |
| Catalog number | 1083665 |
| Category | Patch panel fibre optic |
| Minimum order | 1 Pcs |
| Document ID | EO-521F3FF44B |
| Generated | 2026-11-19 |

## Product Overview

DIN rail splice box, fully mounted ready to splice, for 6x LC duplex (OS2)
Splice box, construction: Rail mounting module, protection index: IP20, material: Metal, connection type: Splice, cable output: up and down, housing size: 1, color: gray, Ethernet

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1083665
Packing unit 1 pc
Catalog page Page 381 (C-2-2019)
GTIN 4055626819518
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85367000
Country of origin DE (Germany)
Drawings
Ambient conditions
Material
Standards and Regulations
Dimensions

General
Connection data
Drawings
Dimensional drawing
DIN rail splice box 6x LC duplex OS2, fully mounted ready to splice
Back to topDimensions
External cable diameter 6 mm ... 12 mm
Back to topAmbient conditions
Ambient temperature (operation) -25 °C ... 70 °C
Ambient temperature (assembly) 0 °C ... 50 °C
Back to topGeneral
Tightening torque nut hand tight
Insertion/withdrawal cycles >= 500
Mounting type DIN rail mounting
Degree of protection IP20
Back to topMaterial
Color traffic grey A RAL 7042
Flammability rating according to UL 94 V0
Back to topConnection data
Connection method Cable gland M20
Cable type Single-mode fiberglass
Back to topStandards and Regulations
Flame resistance yes
Resistance to UV radiation yes
Halogen-free yes
Flammability rating according to UL 94 V0
Shock DIN EN 61300-2-9: 2015-09
Assignment plan International
Back to top

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-FDX20-PP-LCD6-OSA-PT9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.