INDUSTRIAL COMPONENT DATA

FOC-FDX20-PP-LCQ6-OM2-PT9 1019709 PHOENIX CONTACT Spleißbox

Brand: PHOENIX CONTACT | Manufacturer Part Number: FOC-FDX20-PP-LCQ6-OM2-PT9



Manufacturer	PHOENIX CONTACT
MPN / Reference	FOC-FDX20-PP-LCQ6-OM2-PT9
Catalog number	1019709
Category	Patch panel fibre optic
Minimum order	1 Pcs
Document ID	EO-B560DED798
Generated	2026-11-18

Product Overview

Spleißbox
Splice box, construction: Rail mounting module, protection index: IP20, material: Metal, connection type: Splice, cable output: up and down, housing size: 1, color: gray, Ethernet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1019709
Packing unit 1 pc
GTIN 4055626701059
Weight per Piece (excluding packing) 742.650 g
Custom tariff number 85367000
Country of origin DE (Germany)
Mechanical characteristics
Number of slots 12
Connection profile LC connectors
Fiber type GOF
Ferrule diameter 1.25 mm
Insertion/withdrawal cycles >= 500

Connection method Cable gland M20
External cable diameter 6 mm ... 12 mm
Cable outlet above and below
Type of cable For all common cable types
Cable structure Semi-loose compact wires (STB)
Color traffic grey A RAL 7042
Mounting type DIN rail mounting
Degree of protection IP20
Type Rail-mountable module
No. of cable outlets 2
Type of the screw connection M20 x 1.5
Type of note Order information:
Note In addition, shrink splice protection (Order No.: 1019676) or crimp splice protection (Order No.: 1019678) must be ordered separately.
Ambient conditions
Ambient temperature (operation) -25 °C ... 70 °C
Ambient temperature (assembly) 0 °C ... 50 °C
Degree of protection IP20 (according to IEC 60529)
Material data
Flammability rating according to UL 94 V0
Housing material Sheet steel
Housing surface material Powder-coated, gray
Ferrule material Zirconia ceramics
Housing width 40 mm
Depth 115 mm
Height 130 mm
Line characteristics
Type of cable For all common cable types
Cable type Multimode fiberglass
Cable structure Semi-loose compact wires (STB)
Wire colors Color coded
Transmission medium FO
Number of fibers 24
Fiber type Multi-mode 50/125 µm fibergla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FOC-FDX20-PP-LCQ6-OM2-PT9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.