INDUSTRIAL COMPONENT DATA

FP 0,8/ 12-FV-SH 7,85 1043682 PHOENIX CONTACT Plug SMD apantallada, rated Current at 20 °C: 1.7 A, test Volt..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 0,8/ 12-FV-SH 7,85

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FP 0,8/ 12-FV-SH 7,85
Catalog number	1043682
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-7F1BC2358D
Generated	2026-11-19

Product Overview

Plug SMD apantallada, rated Current at 20 °C: 1.7 A, test Voltage: 500 V AC, number of poles: 12, pitch: 0.8 mm, color: black, assembly: Soldering SMD
Shielded SMD plug pin, rated current: 1.7 A, test voltage: 500 VAC, number of poles: 12, pitch: 0.8 mm, color: black, surface contacts: Gold, contact type: Female, mounting: SMD solder

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 0,8/ 12-FV-SH 7,85 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.