INDUSTRIAL COMPONENT DATA

FP 0,8/ 32-FV-SH 4,85 1043711 PHOENIX CONTACT Shielded SMD plug pin, rated current: 1.7 A, Test voltage: 500..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 0,8/ 32-FV-SH 4,85

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FP 0,8/ 32-FV-SH 4,85
Catalog number	1043711
Category	Printed circuit board connector
Minimum order	500 Pcs
Document ID	EO-AFDC826AC1
Generated	2026-11-18

Product Overview

Shielded SMD plug pin, rated current: 1.7 A, Test voltage: 500 V AC, number of poles: 32, pitch: 0.8 mm, color: black, contact surface: Au, contact connection type: Female, mounting: SMD welding
Shielded SMD plug plug, Rated current with 20 °C: 1.7 A, Test voltage: 500 V AC, number of poles: 32, pitch: 0.8 mm, color: black, surface contacts: Gold, mounting: SMD welding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 0,8/ 32-FV-SH 4,85 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.