INDUSTRIAL COMPONENT DATA

FP 0,8/ 32-MV-SH 1,15 1043787 PHOENIX CONTACT Strip blades SMD apantallada, rated Current at 20 °C: 1.7 A, t..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FP 0,8/ 32-MV-SH 1,15

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FP 0,8/ 32-MV-SH 1,15
Catalog number	1043787
Category	Printed circuit board connector
Minimum order	500 Pcs
Document ID	EO-3A6C7F114E
Generated	2026-11-19

Product Overview

Strip blades SMD apantallada, rated Current at 20 °C: 1.7 A, test Voltage: 500 V AC, number of poles: 32, step: 0.8 mm, color: black, surface contacts: Gold, assembly: Soldering SMD
Shielded SMD blade strip, rated current: 1.7 A, Test voltage: 500 VAC, number of poles: 32, pitch: 0.8 mm, color: black, contact surface: Gold, contact type: Male, mounting: SMD welding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FP 0,8/ 32-MV-SH 1,15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.