INDUSTRIAL COMPONENT DATA

# FQ 2,54D/ 30-SH-0-BT 1156905 PHOENIX CONTACT SMD socket, rated current: 3 A, Test voltage: 500 V AC, number ..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: FQ 2,54D/ 30-SH-0-BT**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | FQ 2,54D/ 30-SH-0-BT |
| Catalog number | 1156905 |
| Category | Printed circuit board connector |
| Minimum order | 130 Pcs |
| Document ID | EO-A2ACC35263 |
| Generated | 2026-11-19 |

## Product Overview

SMD socket, rated current: 3 A, Test voltage: 500 V AC, number of poles: 30, pitch: 2.54 mm, color: black, contact surface: Au, contact connection type: Female, mounting: SMD welding
SMD socket, Rated current with 20 °C: 3 A, Test voltage: 500 V AC, number of poles: 30, pitch: 2.54 mm, colour: black, surface contacts: Gold, contact type: Connection female

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FQ 2,54D/ 30-SH-0-BT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.