INDUSTRIAL COMPONENT DATA

FS 0,635/ 40-MV-R- 8,0 1332125 PHOENIX CONTACT SMD blade strip, rated current: 0.5 A, test voltage: 500 V AC..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FS 0,635/ 40-MV-R-8,0

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FS 0,635/ 40-MV-R-8,0
Catalog number	1332125
Category	Printed circuit board connector
Minimum order	600 Pcs
Document ID	EO-7CF8BD198F
Generated	2026-11-19

Product Overview

SMD blade strip, rated current: 0.5 A, test voltage: 500 V AC, number of poles: 40, pitch: 0.635 mm, color: black, contact surface: Au, contact connection type: Male, mounting: SMD welding
SMD blade strip, rated current: 0.5 A, Test voltage: 500 V AC, number of poles: 40, pitch: 0.635 mm, colour: black, surface contacts: Gold

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FS 0,635/ 40-MV-R-8,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.