INDUSTRIAL COMPONENT DATA

FTP-3/4SL 1030004 PHOENIX CONTACT Test plug, nom. voltage: 400 V, number of positions: 4, width: 56.8 mm, he..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTP-3/4SL



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTP-3/4SL
Catalog number	1030004
Category	Test plug for terminal blocks
Minimum order	1 Pcs
Document ID	EO-CC16AB6928
Generated	2026-11-18

Product Overview

Test plug, nom. voltage: 400 V, number of positions: 4, width: 56.8 mm, height: 98.2 mm, color: gray
Test plug, rated voltage: 400 V, rated current: 20 A, number of poles: 4, connection type: Connection by terminal, Sizing cross-section: 2.5 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 1030004
Packing unit 1
Catalog page Page 645 (C-1-2019)
GTIN 4055626532523
Custom tariff number 85366990
Drawings
Dimensions
Mounting
Classifications
General
Connection data
Standards and Regulations

Drawings
Circuit diagram
Back to topGeneral
Number of positions 4
Potentials 4
Nominal cross section 6 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 20 A
Current Ith 20 A
Nominal voltage UN 400 V
Back to topDimensions
Width 56.8 mm
Length 96.8 mm
Height 98.2 mm
Pitch 8.2 mm
Back to topConnection data
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 14
Back to topMounting
Min. tightening torque of the test socket screw: 0.5 Nm
Max. tightening torque of the test socket screw: 0.6 Nm
Back to topStandards and Regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.1 27141100
eCl@ss 6.0 27141100
eCl@ss 7.0 27440313
eCl@ss 8.0 27440313
eCl@ss 9.0 27440313
Back to topETIM
ETIM 4.0 EC000897
ETIM 5.0 EC002255
ETIM 6.0 EC002255
ETIM 7.0 EC002255
Back to topUNSPSC
UNSPSC 13.2 39121410
UNSPSC 18.0 39121410
UNSPSC 19.0 39121410
UNSPSC 20.0 39121410
UNSPSC 21.0 39121410
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTP-3/4SL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.