INDUSTRIAL COMPONENT DATA

# FTP-3/4SL GN 1030003 PHOENIX CONTACT Test plug, nom. voltage: 400 V, number of positions: 4, width: 56.8 mm,..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: FTP-3/4SL GN**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | FTP-3/4SL GN |
| Catalog number | 1030003 |
| Category | Test plug for terminal blocks |
| Minimum order | 1 Pcs |
| Document ID | EO-0AC6E13AB6 |
| Generated | 2026-11-19 |

## Product Overview

Test plug, nom. voltage: 400 V, number of positions: 4, width: 56.8 mm, height: 98.2 mm, color: green
Test connector, nominal voltage: 400 V, number of poles: 4, Sizing cross-section: 2.5 mm², colour: green

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Enclosures connectivity |

## Additional Product Information

Key Commercial Data
Orderkey 1030003
Packing unit 1
Catalog page Page 645 (C-1-2019)
GTIN 4055626532912
Custom tariff number 85366990
Drawings
Dimensions
Mounting
Classifications
General
Connection data
Standards and Regulations
Drawings

Circuit diagram
Back to topGeneral
Number of positions 4
Potentials 4
Nominal cross section 6 mm²
Color green
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 20 A
Current Ith 20 A
Nominal voltage UN 400 V
Back to topDimensions
Width 56.8 mm
Length 96.8 mm
Height 98.2 mm
Pitch 8.2 mm
Back to topConnection data
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 14
Back to topMounting
Min. tightening torque of the test socket screw: 0.5 Nm
Max. tightening torque of the test socket screw: 0.6 Nm
Back to topStandards and Regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.1 27141100
eCl@ss 6.0 27141100
eCl@ss 7.0 27440313
eCl@ss 8.0 27440313
eCl@ss 9.0 27440313
Back to topETIM
ETIM 4.0 EC000897
ETIM 5.0 EC002255
ETIM 6.0 EC002255
ETIM 7.0 EC002255
Back to topUNSPSC
UNSPSC 13.2 39121410
UNSPSC 18.0 39121410
UNSPSC 19.0 39121410
UNSPSC 20.0 39121410
UNSPSC 21.0 39121410
Back to top

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTP-3/4SL GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.