

INDUSTRIAL COMPONENT DATA

DT 6/2,5-DREHSI (5X20) 3034248 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DT 6/2,5-DREHSI (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	DT 6/2,5-DREHSI (5X20)
Catalog number	3034248
Category	Fuse terminal block
Minimum order	25 Pcs
Document ID	EO-C05AD2A3EA
Generated	2026-09-21

Product Overview

Fuse modular terminal block

Fuse terminal block, for fuse cartridge G, cross-section: 0.5-10 mm², AWG: 20-8, width: 12.2 mm, colour: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3034248

Packing unit 25 pc

Minimum order quantity 25 pc

Catalog page Page 212 (CL-2009)

GTIN 4046356052795

Weight per Piece (excluding packing) 24.430 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 2.5 mm²

Color black

Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 0.77 W
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Maximum load current 10 A (with 4 mm² conductor cross section)
Nominal current I_N 10 A
Nominal voltage U_N 500 V
Connection in acc. with standard IEC 60947-7-1
Maximum load current (upper level) 10 A
Nominal current I_N(upper level) 10 A
Nominal voltage U_N 500 V
Rated operating voltage 250 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 2, bogie-mounted
Test frequency f₁= 5 Hz to f₂= 250 Hz
ASD level 6.12 (m/s²)²/Hz
Acceleration 3.12 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DT 6/2,5-DREHSI (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.