

## INDUSTRIAL COMPONENT DATA

# UK 10-DREHSELED 12 (5X20) 3005112 PHOENIX CONTACT

## Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10-DREHSELED 12 (5X20)



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | PHOENIX CONTACT           |
| MPN / Reference | UK 10-DREHSELED 12 (5X20) |
| Catalog number  | 3005112                   |
| Category        | Fuse terminal block       |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-8F2EF97D62             |
| Generated       | 2026-09-22                |

### Product Overview

Fuse modular terminal block

Fuse terminal block, for fuse cartridge G, cross-section: 0.5 - 16 mm<sup>2</sup>, AWG: 24 - 6, width: 12 mm, colour: Black

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Modular TBs

### Additional Product Information

Key Commercial Data

Orderkey 3005112

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 458 (C-1-2017)

GTIN 4017918091057

Weight per Piece (excluding packing) 33.770 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 16 mm<sup>2</sup>

Color black

Insulating material PA  
Flammability rating according to UL 94 V2  
Maximum power dissipation for nominal condition 2.43 W  
Fuse G / 5 x 20  
Fuse type Glass / ceramics / ...  
Rated surge voltage 4 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
LED voltage range 5 V AC/DC ... 15 V AC/DC  
LED current range 0.5 mA ... 2.5 mA  
Connection in acc. with standard IEC 60947-7-3  
Maximum load current 10 A  
Nominal current I<sub>N</sub> 10 A  
Nominal voltage U<sub>N</sub> 500 V  
800 V (As a disconnect terminal block)  
Open side panel No  
Oscillation, broadband noise test result Test passed  
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03  
Test spectrum Service life test category 1, class B, body mounted  
Test frequency f<sub>1</sub>= 5 Hz to f<sub>2</sub>= 150 Hz  
ASD level 1.857 (m/s<sup>2</sup>)<sup>2</sup>/Hz  
Acceleration 0,8 g  
Test duration per axis 5 h  
Test directions X-, Y- and Z-axis  
Shock test result Test passed  
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03  
Shock form Half-sine  
Acceleration 5 g  
Shock duration 30 ms  
Number of shocks per direction 3  
Test directions X-, Y- and Z-axis (pos. and neg.)  
Relative insulation material temperature....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10-DREHSEILED 12 (5X20) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.