

INDUSTRIAL COMPONENT DATA

UK 5-HESILED 24 3004126 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-HESILED 24



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 5-HESILED 24
Catalog number	3004126
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-22F755DCE4
Generated	2026-09-22

Product Overview

Fuse modular terminal block

Rail terminal for fuse, fuse type: Glass/ceramic/..., fuse type: G/5 x 20/5 x 25/5 x 30, nominal voltage: 24 V, nominal current: 6.3 A, number of poles: 1, connection type: Screw connection, Dimensioning section: 1 mm², section: 0.2 mm²- 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 5 x 20 / 5 x 25 / 5 x 30, nom. voltage: 24 V, nominal current: 6.3 A, number of positions: 1, connection method: Screw connection, Rated cross section: 1 mm², cross section: 0.2 mm²- 4 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Technical dataNotesNote regarding marking For terminal marking, please use marking material with 8.2 mm pitch.

Note regarding marking For lever marking, please use marking material with 6.2 mm pitch.

Notes on operation The current is determined by the fuse used, the voltage by the selected LED.

If the fuse is faulty, the downstream circuit will not be disconnected.

Product propertiesProduct type Fuse terminal block

Number of positions 1

Number of connections 2

Number of rows 1

Potentials 1

Data management status
Article revision 12
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical properties Fuse type Glass / ceramics / ...
Rated surge voltage 8 kV
Maximum power dissipation for nominal condition 1.02 W
Fuse G / 5 x 20 / 5 x 25 / 5 x 30
LED voltage range 15 V AC/DC ... 30 V AC/DC
LED current range 3.5 mA ... 8.1 mA
Input data LED voltage range 15 V AC/DC ... 30 V AC/DC
Connection data Number of connections per level 2
Nominal cross section 4 mm²
Level 1 above 1 below 1
Screw thread M3
Tightening torque 0.6 ... 0.8 Nm
Stripping length 8 mm
Internal cylindrical gage A4
Connection in acc. with standard IEC 60947-7-3
Conductor cross section rigid 0.2 mm² ... 4 mm²
Cross section AWG 24 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²
Flexible conductor cross se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-HESILED 24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.