

INDUSTRIAL COMPONENT DATA

UK 6,3-HESI 3004171 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 6,3-HESI



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 6,3-HESI
Catalog number	3004171
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-846D6F327C
Generated	2026-09-23

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/6.3 x 32, nominal voltage: 500 V, nominal current: 10 A, number of poles: 1, connection type: Screw connection, Sizing cross-section: 1.5 mm², cross-section: 0.5 mm²- 16 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3004171

Packing unit 50 pc

Catalog page Page 455 (C-1-2017)

GTIN 4017918090685

Weight per Piece (excluding packing) 31.820 g

Custom tariff number 85369095

Country of origin TR (Turkey)

General

Note For terminal marking, please use marking material with 10.2 mm pitch.

For lever marking, please use marking material with 8.2 mm pitch.

Number of levels 1

Number of connections 2
Nominal cross section 16 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 2.43 W
Fuse G / 6,3 x 32
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Maximum load current 10 A
Nominal current I_N 10 A
Nominal voltage U_N 500 V (As a fuse terminal block)
Rated operating voltage 500 V
Open side panel No
Number of positions 1
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 6,3-HESI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.