INDUSTRIAL COMPONENT DATA

USEN 14 N 3048357 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: USEN 14 N



Manufacturer	PHOENIX CONTACT
MPN / Reference	USEN 14 N
Catalog number	3048357
Category	Fuse terminal block
Minimum order	10 Pcs
Document ID	EO-7743C325D6
Generated	2026-11-18

Product Overview

Fuse modular terminal block
Fuse terminals, for NEOZED fuse cartridges
Fuse modular terminal block, fuse type: Screw cartridge, fuse type: D 01 / E 14, nom. voltage: 400 V, nominal current: 16 A, connection method: Screw connection, Rated cross section: 35 mm2, cross section: 1.5 mm2- 35 mm2, mounting type: NS 35/7,5, NS 35/15, color: light gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataNotesNote on application for NEOZED fuse-links
Product propertiesProduct type Fuse terminal block
Pitch 27 mm
Number of connections 2
Number of rows 1
Potentials 1
Data management status
Article revision 00
Insulation characteristics
Overvoltage category III
Degree of pollution 2

Electrical propertiesFuse type Screw cartridge
Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 4.06 W
Fuse D 01 / E 14
Connection dataNumber of connections per level 2
Nominal cross section 35 mm²
Level 1
Screw thread M6
Tightening torque 3.5 ... 4 Nm
Stripping length 19 mm
Internal cylindrical gage B8
Conductor cross section rigid 1.5 mm² ... 35 mm²
Cross section AWG 14 ... 2 (converted acc. to IEC)
Conductor cross section flexible 1.5 mm² ... 35 mm²
Conductor cross section, flexible [AWG] 14 ... 2 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 1.5 mm² ... 25 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 1.5 mm² ... 25 mm²
Cross-section with insertion bridge, rigid 25 mm²
Cross-section with insertion bridge, flexible 25 mm²
2 conductors with same cross section, solid 1.5 mm² ... 10 mm²
2 conductors with same cross section, flexible 1.5 mm² ... 10 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 1.5 mm² ... 10 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 1.5 mm² ... 10 mm²
Nominal current 16 A (the current is de...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USEN 14 N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.