


INDUSTRIAL COMPONENT DATA

UT 4-PE/HESI (5X20) 3073995 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-PE/HESI (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-PE/HESI (5X20)
Catalog number	3073995
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-E37BE3D522
Generated	2026-09-20

Product Overview

Fuse modular terminal block

Fuse terminal block, nominal voltage: 500 V, nominal current: 6.3 A, Screw connection, Dimensioning cross-section: 1 mm², cross-section: 0.14 mm² - 6 mm², installation type: NS 35/7.5, NS 35/15, colour: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3073995

Packing unit 50 pc

Catalog page Page 231 (C-1-2017)

GTIN 4046356416238

Weight per Piece (excluding packing) 25.420 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 1.6 W

Fuse G / 5 x 20

Fuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)

max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)

max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)

max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)

Connection in acc. with standard IEC 60947-7-2/IEC 60947-7-3

Maximum load current 6.3 A (the current is determined by the fuse used)

Nominal current I_N 6.3 A

Nominal voltage U_N 500 V

Open side panel No

Dimensions

Width 6.2 mm

Length 70.8 mm

Height NS 35/7,5 73 mm

Height NS 35/15 80.5 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.14 mm²

Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-PE/HESI (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.