INDUSTRIAL COMPONENT DATA

PT 10,3-HESILED 1000V 3062143 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 10,3-HESILED 1000V



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 10,3-HESILED 1000V
Catalog number	3062143
Category	Fuse terminal block
Minimum order	10 Pcs
Document ID	EO-90BFDAAF7A
Generated	2026-11-18

Product Overview

Fuse modular terminal block
Fuse holder, fuse type: gPV 10.3 x 38 mm according to 60269-6, nominal voltage: 1000 V, nominal current: 20 A, connection type: Push-in connection, Sizing cross-section: 10 mm², cross-section: 1.5 mm²- 10 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3062143
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 115 (C-1-2017)
GTIN 4046356724739
Weight per Piece (excluding packing) 54.840 g
Custom tariff number 85369095
Country of origin CN (China)
General
Number of levels 1
Number of connections 2

Nominal cross section 10 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 3 W
Fuse Midget / 10.3 x 38
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIa
Maximum power dissipation 3 W (Fuse insert)
LED voltage range 250 V AC ... 1000 V AC
Connection in acc. with standard IEC 60269-1/-2
Maximum load current 20 A (the current is determined by the fuse used)
Nominal current IN 20 A (the current is determined by the fuse used)
Nominal voltage UN 1000 V (the voltage is determined by the fuse used)
Open side panel No
Dimensions
Width 17.6 mm
Length 87 mm
Height NS 35/7,5 63 mm
Height NS 35/15 70.5 mm
Connection data
Conductor cross section solid min. 1.5 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 1.5 mm²
Conductor cross section flexible max. 10 mm²
Conductor cross section AWG min. 16
Conductor cross section AWG max. 6
Conductor cross section flexible, with ferrule without plastic sleeve min. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²
Conductor cross section flexible, with ferrul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 10,3-HESILED 1000V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.