

INDUSTRIAL COMPONENT DATA

UT 4-L/HESI (5X20) 3214325 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-L/HESI (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-L/HESI (5X20)
Catalog number	3214325
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-4E56F3BB0C
Generated	2026-09-21

Product Overview

Fuse modular terminal block

Rail terminal for fuse, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 250 V, nominal current: 30 A, connection type: Screw connection, Sizing section: 4 mm², cross-section: 0.14 mm²- 6 mm², connection type: Screw connection, Sizing cross-section: 1 mm², cross-section: 0.14 mm²- 6 mm², Mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3214325

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 232 (C-1-2017)

GTIN 4046356909402

Weight per Piece (excluding packing) 31.770 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Note The current is determined by the fuse used, the voltage by the selected LED.

If the fuse is faulty, the downstream circuit will not be disconnected.

Number of levels 2

Number of connections 4

Nominal cross section 4 mm²

Color black

Insulating material PA

Flammability rating according to UL 94 V0

Maximum power dissipation for nominal condition 0.9 W (the value is multiplied when connecting multiple levels)

Fuse G / 5 x 20

Fuse type Glass / ceramics / ...

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)

max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)

max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)

max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)

Connection in acc. with standard IEC 60947-7-2/IEC 60947-7-3

Maximum load current 36 A (with 6 mm² conductor cross section)

Nominal current IN 28 A (with 4 mm² conductor cross section)

Nominal voltage UN 500 V

Connection in acc. with standard IEC 60947-7-2/IEC 6094...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-L/HESI (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.