INDUSTRIAL COMPONENT DATA

PT 4-FSI/F 3208943 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 4-FSI/F



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 4-FSI/F
Catalog number	3208943
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-75F7287C23
Generated	2026-11-18

Product Overview

Fuse modular terminal block
Fuse terminal block, fuse type: Flat, fuse type: Model F (miniature), nominal voltage: 400 V, nominal current: 10 A, connection type: Push-in connection, Dimensioning cross-section: 4 mm², cross-section: 0.2 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, colour: black
Fuse modular terminal block, fuse type: Flat, fuse type: Type F (miniature), nom. voltage: 400 V, nominal current: 10 A, connection method: Push-in connection, Rated cross section: 4 mm2, cross section: 0.2 mm2- 6 mm2, mounting type: NS 35/7,5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Fuse terminal block
Number of connections 2
Number of rows 1
Potentials 1
Data management status
Article revision 09
Insulation characteristics
Overvoltage category III
Degree of pollution 3

Electrical propertiesFuse type Flat
Rated surge voltage 6 kV
Maximum power dissipation for nominal condition 1.02 W
Fuse Type F (miniature)
Maximum current with single arrangement 15 A
Connection dataNumber of connections per level 2
Nominal cross section 4 mm²
Stripping length 10 mm ... 12 mm
Internal cylindrical gage A4
Conductor cross section rigid 0.2 mm² ... 6 mm²
Cross section AWG 24 ... 10 (converted acc. to IEC)
Conductor cross section flexible 0.2 mm² ... 6 mm²
Conductor cross section, flexible [AWG] 24 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²
Nominal current 10 A (the current is determined by the fuse used)
Maximum load current 15 A (with 6 mm² conductor cross section, rigid)
Nominal voltage 400 V (the voltage is determined by the fuse used)
Nominal cross section 4 mm²
Connection cross sections directly pluggable
Conductor cross section rigid 0.5 mm² ... 6 mm²
Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm² ... 2.5 mm²
Flexible conductor cross sect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 4-FSI/F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.