INDUSTRIAL COMPONENT DATA

ST 4-FSI/C 3036372 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 4-FSI/C



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 4-FSI/C
Catalog number	3036372
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-8B562E5D67
Generated	2026-11-18

Product Overview

Fuse modular terminal block
Fuse terminal block, fuse type: Flat, fuse type: C, nominal voltage: 400 V, nominal current: 30 A, connection type: Spring connection, 1st floor, Sizing cross-section: 4 mm², cross-section: 0.08 mm²- 6 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3036372
Packing unit 50 pc
Catalog page Page 177 (C-1-2017)
GTIN 4017918890445
Weight per Piece (excluding packing) 19.610 g
Custom tariff number 85369095
Country of origin TR (Turkey)
General
Number of levels 1
Number of connections 2
Mounting type NS 35/7,5

Color black
Insulating material PA
Flammability rating according to UL 94 V0
Electrical data
Fuse C
Fuse type Flat
Degree of pollution 3
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Maximum current with single arrangement 30 A
Dimensions
Width 8.2 mm
Height NS 35/7,5 43.5 mm
Height NS 35/15 51 mm
Connection data
Conductor cross section solid min. 0.08 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.08 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 28
Conductor cross section AWG max. 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1 mm²
Connection method Spring-cage connection
Internal cylindrical gage A4
Standards and Regulations
Connecti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 4-FSI/C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.