INDUSTRIAL COMPONENT DATA

UM-DELTAV/D/SI/BFI/TP 5603257 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-DELTAV/D/SI/BFI/TP



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-DELTAV/D/SI/BFI/TP
Catalog number	5603257
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-17E0384F6D
Generated	2026-11-18

Product Overview

Passive module
Fuse module with terminal blocks for connection display and fuse fault indication (for digital cards of the Delta V control)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 5603257
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 483 (C-5-2017)
GTIN 4017918955014
Weight per Piece (excluding packing) 208.900 g
Custom tariff number 85369010
Country of origin US (United States)
Dimensions
Width 61 mm
Height 126 mm
Depth 71 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 24 V DC
Max. perm. current (per branch) 50 mA (in as-supplied state, with one 50 mAF fuse, max. 1 A permitted)
Number of positions 16
Mounting position any
Connection data for connection 1
Connection name Field level
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method IDC/FLK pin strip
Number of connections 1
Number of positions 16
Pitch 2.54 mm
Supported controller
Controller Emerson DeltaV
- suitable I/O card VE4001S2T2B3
VE4001S2T2B3 Series 2
VE4001S2T1B3
VE4002S1T1B3
VE4002S1T2B3
VE4002S1T2B3 Series 2
Standards and Regulations
Connection in acc. with standard CUL
Standards/regulations IEC 60664
DIN EN 50178
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacture...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-DELTAV/D/SI/BFI/TP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.