INDUSTRIAL COMPONENT DATA

# P-FU 6,3X32 LED 24-EX 3046509 PHOENIX CONTACT Fuse plug

**Brand: PHOENIX CONTACT | Manufacturer Part Number: P-FU 6,3X32 LED 24-EX**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | P-FU 6,3X32 LED 24-EX |
| Catalog number | 3046509 |
| Category | Component plug terminal block |
| Minimum order | 10 Pcs |
| Document ID | EO-1F2FFC51C5 |
| Generated | 2026-11-18 |

## Product Overview

Fuse plug
Fuse holder, Before replacing the fuse G, remove the fuse holder head from the base terminal., rated current: 10 A, fuse type: G/6.3 x 32, color: black

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3046509
Packing unit 10 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 244 (C-1-2017)
GTIN 4046356919265
Weight per Piece (excluding packing) 6.600 g
Custom tariff number 85369095
Country of origin PL (Poland)
General
Note Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block.
Number of levels 1

Color black
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Machine building
Plant engineering
Dimensions
Width 8.2 mm
Length 40 mm
General
Fuse G / 6,3 x 32
Fuse type Sand filled
Degree of pollution 3
Maximum power dissipation 1.6 W
LED voltage range 12 V DC ... 30 V DC
LED current range 0.31 mA ... 0.95 mA
Maximum load current 10 A (the current is determined by the fuse used)
Nominal current IN 10 A (the current is determined by the fuse used)
Open side panel No
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027141145eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141149eCl@ss 8.027141149eCl@ss 9.027141149
ETIM 2.0EC000897ETIM 3.0EC000897ETIM 4.0EC000899ETIM 5.0EC002018ETIM 6.0EC002018
UNSPSC 6.0130211811UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-FU 6,3X32 LED 24-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.