

**INDUSTRIAL COMPONENT DATA**

# UK 10,3-HESI 1000V 3211236 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-HESI 1000V



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | UK 10,3-HESI 1000V  |
| Catalog number  | 3211236             |
| Category        | Fuse terminal block |
| Minimum order   | 12 Pcs              |
| Document ID     | EO-302C49521C       |
| Generated       | 2026-09-20          |

## Product Overview

Fuse modular terminal block

Fuse holder, fuse type: Glass/ceramic/..., fuse type: gPV 10.3 x 38 mm according to 60269-6, nominal voltage: 1000 V, nominal current: 30 A, connection type: Screw connection, Sizing cross-section: 16 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, colour: black

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3211236

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 464 (C-1-2017)

GTIN 4046356482394

Weight per Piece (excluding packing) 50.950 g

Custom tariff number 85369095

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 25 mm<sup>2</sup>  
Color black  
Insulating material PA  
Flammability rating according to UL 94 V0  
Maximum power dissipation for nominal condition 3.26 W  
Fuse 10:3 x 38 mm  
Fuse type Glass / ceramics / ...  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category II  
Insulating material group IIIa  
Connection in acc. with standard IEC 60269-1/-2  
Maximum load current 30 A (the current and voltage are determined by the fuse)  
Nominal current I<sub>N</sub> 30 A (the current and voltage are determined by the fuse)  
Nominal voltage U<sub>N</sub> 1000 V DC (the current and voltage are determined by the fuse)  
Open side panel No  
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11  
Back of the hand protection guaranteed  
Finger protection guaranteed  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 120 °C  
Dimensions  
Width 18 mm  
Length 81 mm  
Height NS 35/7,5 65.5 mm  
Height NS 35/15 73 mm  
Connection data  
Conductor cross section solid min. 1.5 mm<sup>2</sup>  
Conductor cross section solid max. 25 mm<sup>2</sup>  
Conductor cross section flexible min. 0.75 mm<sup>2</sup>  
Conductor cross section flexible max. 25 mm<sup>2</sup>  
Conductor cross section AWG min. 16  
Conductor cross section AWG max. 3  
Conductor cross sec...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-HESI 1000V with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.