

INDUSTRIAL COMPONENT DATA

G-INS-M40-L68N-PNES-GY 1424479 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-M40-L68N-PNES-GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-M40-L68N-PNES-GY
Catalog number	1424479
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-6C181DF266
Generated	2026-09-23

Product Overview

Cable gland

Cable gland, screw connection material: PA, cable outer diameter 22 mm ... 32 mm, shielding: no, connection thread: M40 x 1.5, colour: silver grey RAL 7001

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1424479

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 694 (C-2-2017)

GTIN 4055626372693

Weight per Piece (excluding packing) 77.170 g

Custom tariff number 39269097

Country of origin TR (Turkey)

Dimensions

Length 55 mm

Wrench size, union nut 53 mm

Wrench size, support 53 mm

Hexagon angular dimension 52 mm

Length of the connecting thread 18 mm

Feed-through hole diameter 40.1 mm ... 40.3 mm

External cable diameter 22 mm ... 32 mm

22 mm ... 32 mm (for UL 514 B)

Ambient conditions

Degree of protection IP68 (5 bar / 0.5 h)

IP66

Ambient temperature (operation) -20 °C ... 100 °C (static)

General

No. of conductors 1

Cable gland material PA

Cable seal material Neoprene

Flammability rating according to UL 94 V2

V2 (Housing)

Shielded no

Thread type connection side M40 x 1.5

Thread type on connection side M40

Torque 5 Nm (Union nut: EN 62444)

5 Nm (Support: EN 62444)

20 Nm (for UL514 B: union nut)

Color gray

Impact category 4

Execution of the strain relief A

Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque

Manufacturer BIMED

Manufacturer Designation BM-08

Standards and Regulations

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127149109eCl@ss 6.027149100eCl@ss 7.02714910...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-M40-L68N-PNES-GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.