INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/3,0-PUR/C-1L-Z 1400787 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/3,0-PUR/C-1L-Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/3,0-PUR/C-1L-Z
Catalog number	1400787
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-D44FCA73E4
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, M12 straight connector, coding: A, with 1 LED, connected with Diode Z, to Valve connectors C (8mm), with 1 LED, connected with Diode Z, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1400787
Packing unit 1
GTIN 4046356511605
Custom tariff number 85444290
Dimensions
Length of cable 3 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
-20 °C ... 85 °C (valve plug)
Degree of protection IP65
IP67
General

Rated current at 40°C 4 A
Rated voltage 24 V AC
24 V DC
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Valve connector EN 175301-803
Status display 1 LED
Protective circuit/component Z diode
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6.6
Material housing valve plug TPU
Material, knurls Zinc die-cast, nickel-plated
Sealing material TPU (Seal molded)
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Standard designation Valve connector
Standards/regulations EN 175301-803
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 3x 0.5 mm²
AWG signal line 20
Conductor structure signal line 28x 0.15 mm
Core diameter including insulation 1.5 mm ±0.05 mm (Signal line)
W...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/3,0-PUR/C-1L-Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.