
INDUSTRIAL COMPONENT DATA

GMSTB 2,5/ 2-G-7,62 CR1 1713478 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5/ 2-G-7,62 CR1



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTB 2,5/ 2-G-7,62 CR1
Catalog number	1713478
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-3AE4441EA4
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 630 V, contact surface: Tin, contact type: Male, Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, number of connections: 2, family of articles: GMSTB 2.5/.. -G, pitch: 7.62 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.2 mm, Stecksystem: CLASSIC COMBICON, Locking: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1713478
Packing unit 1
GTIN 4055626372518
Custom tariff number 85366930
Dimensions
Length [l] 11.8 mm
Width 13.44 mm
Pitch 7.62 mm
Dimension a 7.62 mm

Width [w] 13.44 mm
Height [h] 11.8 mm
Height 8.6 mm
Length of the solder pin 3.2 mm
Pin dimensions 1 x 1 mm
Length 11.8 mm
General
Range of articles GMSTB 2,5/..-G
Insulating material group I
Rated voltage (III/2) 630 V
Nominal current IN 12 A
Flammability rating according to UL 94 V0
Color green
Number of positions 2
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 5.0EC002637ETIM 6.0EC002637

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5/ 2-G-7,62 CR1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.