INDUSTRIAL COMPONENT DATA

RB 16-6 3047072 PHOENIX CONTACT Reducing bridge

Brand: PHOENIX CONTACT | Manufacturer Part Number: RB 16-6



Manufacturer	PHOENIX CONTACT
MPN / Reference	RB 16-6
Catalog number	3047072
Category	Cross-connector for terminal block
Minimum order	10 Pcs
Document ID	EO-8633B4DFDB
Generated	2026-11-18

Product Overview

Reducing bridge
Reduction bridge, pitch: 12.2 mm, colour: red
Reducing bridge, pitch: 12.2 mm, number of positions: 2, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Reducing bridge
Number of positions 2
Pitch 12.2 mm
Data management status
Article revision 02
Electrical propertiesMaximum load current 37 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
Connection dataMaximum load current 37 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
DimensionsPitch 12.2 mm
Material specificationsColor red (RAL 3001)
Material Copper
Flammability rating according to UL 94 V0

Insulating material PA
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C ()
Permissible humidity (storage/transport) 30 % ... 70 %
MountingMounting type Plug-in mounting

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RB 16-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.