INDUSTRIAL COMPONENT DATA

GW DEVICE SERVER 1E/2DB9 2702760 PHOENIX CONTACT Interface converters

Brand: PHOENIX CONTACT | Manufacturer Part Number: GW DEVICE SERVER 1E/2DB9



Manufacturer	PHOENIX CONTACT
MPN / Reference	GW DEVICE SERVER 1E/2DB9
Catalog number	2702760
Category	PLC communication module
Minimum order	1 Pcs
Document ID	EO-9617D6CD67
Generated	2026-11-18

Product Overview

Interface converters
Serial device server for the conversion of serial data (RS-232/422/485) to Ethernet data (RJ45). Compatible with TCP and UDP protocols. COM port redirection software and Windows drivers can be downloaded. It comprises one RJ45 connection and two D-SUB-9 connections.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data
Orderkey 2702760
Packing unit 1 pc
Catalog page Page 342 (C-6-2017)
GTIN 4055626339160
Weight per Piece (excluding packing) 125.000 g
Custom tariff number 85176200
Country of origin US (United States)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 22.5 mm

Height 99 mm
Depth 115 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Permissible humidity (operation) 10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Altitude < 2000 m
Degree of protection IP20
Noise immunity EN 61000-6-2:2005
General
Electrical isolation IEC UL 61010-1 (VCC // Ethernet)
Test voltage data interface/data interface 1.5 kVrms(50 Hz, 1 min.)
Test voltage data interface/power supply 1.5 kVrms
1.5 kVrms(50 Hz, 1 min.)
Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU
Noise emission EN 61000-6-4
Net weight 125 g
Housing material PA 6.6
Color gray
MTBF 69.4 Years (Telcordia standard, 25°C temperature, 50% stress, Environmental Factor = 1.0)
46.3 Years (Telcordia standard, 40°C temperature, 50% stress, environmental factor = 1.0)
Conformance CE-compliant
UL, USA UL 61010-1
UL, USA/Canada Class I, Div. 2, Groups A, B, C, D T4A
Power supply
Supply voltage range 10.8 V DC ... 30 V DC (via pluggable COMBICON screw terminal block)
Max. current consumption 85 mA (24 V DC)
Typ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GW DEVICE SERVER 1E/2DB9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.