
INDUSTRIAL COMPONENT DATA

TVFKC 1,5/ 4-ST YECPLPD:I4-I7 1702597 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: TVFKC 1,5/ 4-ST YECPLPD:I4-I7



Manufacturer	PHOENIX CONTACT
MPN / Reference	TVFKC 1,5/ 4-ST YECPLPD:I4-I7
Catalog number	1702597
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-C806A9E0A0
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 1.5 mm², color: yellow, nominal current: 10 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 8, family of articles: TVFKC 1.5/.. -ST, pitch: 5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1702597
Packing unit 1
GTIN 4046356596596
Custom tariff number 85366990
Dimensions
Length [l] 23.3 mm
Width [w] 20 mm
Height [h] 15 mm
Pitch 5 mm

Dimension a 15 mm
General
Range of articles TVFKC 1,5/..-ST
Number of positions 4
Connection method Push-in spring connection
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 10 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
Standards and Regulations
Connection in acc. with standard EN-VDE
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309
ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002638ETIM 6.0EC002638
UNSPSC 6.0130211801UNSPSC 7.090139121...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TVFKC 1,5/ 4-ST YECPLPD:I4-I7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.