INDUSTRIAL COMPONENT DATA

GMVSTBR 2,5/ 5-STF-7,62 3PA 1104258 PHOENIX CONTACT Connector for printed circuit board, nominal current: 12..

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMVSTBR 2,5/ 5-STF-7,62 3PA

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	GMVSTBR 2,5/ 5-STF-7,62 3PA
Catalog number	1104258
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-49738042B7
Generated	2026-11-18

Product Overview

Connector for printed circuit board, nominal current: 12 A, number of poles: 3, pitch: 7.62 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface contacts: Tin
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 630 V, contact surface: Tin, contact type: Female connection, Number of rows: 1, Number of poles per row: 3, family of articles: GMVSTBR 2.5/.. -STF, pitch: 7.62 mm, connection type: Screw connection with traction capsule, conductor connection direction/printed circuit board: 90 °, Stecksystem: CLASSIC COMBICON, Locking: Screw lock, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMVSTBR 2,5/ 5-STF-7,62 3PA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.