INDUSTRIAL COMPONENT DATA

GMVSTBW 2,5/ 6-ST BD:NC 1071431 PHOENIX CONTACT Connector for printed circuit board, number of poles: 6, pit..

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMVSTBW 2,5/ 6-ST BD:NC



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMVSTBW 2,5/ 6-ST BD:NC
Catalog number	1071431
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-BC91BD63D8
Generated	2026-11-19

Product Overview

Connector for printed circuit board, number of poles: 6, pitch: 7.5 mm, color: green
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of rows: 1, number of poles: 6, family of articles: GMVSTBW 2.5/.. -ST, pitch: 7.5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: -90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataItem PropertiesProduct Type Printed Circuit Board Connector
Product Family GMVSTBW 2,5/.. -ST
Product Line COMBICON Connectors M
Number of poles 6
Step 7.5 mm
Number of rows 1
Data Maintenance Status
Article Review 01
Electrical PropertiesNominal Current IN 12 A
Nominal voltage UN 630 V

Contact resistance 2.2 m?
Sizing voltage (III/3) 500 V
Dimensioning transient voltage (III/3) 6 kV
Dimensioning voltage (III/2) 630 V
Dimensioning Transient Voltage (III/2) 6 kV
Nominal voltage (II/2) 1000 V
Dimensioning transient voltage (II/2) 6 kV
Connection dataConnection technology
Construction Standard
Connector System COMBICON MSTB 2.5
Nominal Section 2.5 mm²
Contact Connection Type Female
Blockade
Locking system without
Clamping flange without
Connecting Conductors
Connection type Screw connection with traction capsule
Connection Direction Driver/PCB -90 °
Rigid conductor section 0.2 mm² ... 2.5 mm²
Flexible conductor section 0.2 mm² ... 2.5 mm²
AWG Conductor Section 24 ... 12
Flexible conductor section with toe cap, without plastic sleeve 0.25 mm² ... 2.5 mm²
Flexible conductor section with toe cap, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with the same cross-section, rigid 0.2 mm² ... 1 mm²
2 conductors with the same cross-section, flexible 0.2 mm² ... 1.5 mm²
2 conductors of equal cross-section, flexible with toe cap, without plastic sleeve 0.25 mm² ... 1 mm²
2 conductors with the same cross-section, flexible with TWIN toe cap with plastic sleeve 0.5 mm²....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMVSTBW 2,5/ 6-ST BD:NC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.