
INDUSTRIAL COMPONENT DATA

UT 4-PE/L/N 3214361 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-PE/L/N



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-PE/L/N
Catalog number	3214361
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-A8E759EF9A
Generated	2026-11-18

Product Overview

Ground modular terminal block
Ground terminal, nominal voltage: 500 V, nominal current: 30 A, number of connections: 5, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², Screw connection, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3214361
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 230 (C-1-2017)
GTIN 4046356895705
Weight per Piece (excluding packing) 31.350 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 3
Number of connections 5

Potentials 3
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)
Maximum load current 36 A (with 6 mm² conductor cross section)
Nominal current IN 30 A
Nominal voltage UN 500 V
Maximum load current 36 A (with 6 mm² conductor connection)
Nominal current IN 30 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel No
Dimensions
Width 6.2 mm
Length 92.7 mm
Height 60.1 mm
Height NS 35/7,5 61.7 mm
Height NS 35/15 69.2 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Screw thread M3
Stripping length 9 mm
Tightening torque, min 0.6 Nm
Tightening torque max 0.8 Nm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 10
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flex...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-PE/L/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.