INDUSTRIAL COMPONENT DATA

UKH 70-PE/S 3213141 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKH 70-PE/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKH 70-PE/S
Catalog number	3213141
Category	Ground terminal block
Minimum order	10 Pcs
Document ID	EO-C654C8ABC0
Generated	2026-11-18

Product Overview

Ground modular terminal block
Ground terminal, number of connections: 2, number of poles: 1, connection type: Screw connection, Sizing cross-section: 70 mm², cross-section: 16 mm² - 95 mm², fixing type: PE foot with fixing screw, M6, mounting class: NS 35/7.5, NS 35/15, NS 35/15-2.3, NS 32, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3213141
Packing unit 10 pc
Catalog page Page 259 (C-1-2017)
GTIN 4046356783446
Weight per Piece (excluding packing) 198.000 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of positions 1
Number of levels 1
Number of connections 2

Nominal cross section 70 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Open side panel No
Terminal block mounting 6 Nm ... 8 Nm (PE foot with mounting screw, M6)
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f1= 5 Hz to f2= 150 Hz
ASD level 1.857 (m/s2)2/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 5 g
Shock duration 30 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKH 70-PE/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.