
INDUSTRIAL COMPONENT DATA

UT 4-PE/L/TG 3214365 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-PE/L/TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-PE/L/TG
Catalog number	3214365
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-536231D962
Generated	2026-11-19

Product Overview

Ground modular terminal block
Ground terminal, Current and voltage are determined by the connector used., nominal voltage: 500 V, nominal current: 28 A, connection type: Screw connection, Sizing section: 4 mm², section: 0.14 mm² - 6 mm², connection type: Screw connection, Sizing section: 2.5 mm², section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3214365
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 232 (C-1-2017)
GTIN 4046356895712
Weight per Piece (excluding packing) 31.610 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 3
Number of connections 5

Potentials 3
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)
Maximum load current 36 A (with 6 mm² conductor cross section)
Nominal current IN 28 A
Nominal voltage UN 500 V
Maximum load current 20 A (with 6 mm² conductor connection)
Nominal current IN 20 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f1= 5 Hz to f2= 150 Hz
ASD level 0.964 (m/s2)2/Hz
Acceleration 0.58 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-PE/L/TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.