INDUSTRIAL COMPONENT DATA

# PT 10-TWIN-PE 3208745 PHOENIX CONTACT Ground modular terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 10-TWIN-PE**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PT 10-TWIN-PE |
| Catalog number | 3208745 |
| Category | Ground terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-12F50498CD |
| Generated | 2026-11-18 |

## Product Overview

Ground modular terminal block
Ground terminal, number of connections: 3, connection type: Push-in connection, Sizing cross-section: 10 mm², cross-section: 0.5 mm² - 16 mm², mounting class: NS 35/7.5, NS 35/15, color: yellow-green
Terminals for earth conductors, number of connections: 3, connection type: Push-in connection, Dimensioning cross-section: 10 mm2, cross-section: 0.5 mm2 - 16 mm2, mounting type: NS 35/7.5, NS 35/15, colour: yellow-green

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3208745
Packing unit 50 pc
Catalog page Page 115 (C-1-2017)
GTIN 4046356643603
Weight per Piece (excluding packing) 44.180 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of levels 1
Number of connections 3

Nominal cross section 10 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 2, bogie-mounted
Test frequency f1= 5 Hz to f2= 250 Hz
ASD level 6.12 (m/s2)2/Hz
Acceleration 3.12 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 30g
Shock duration 18 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behav...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 10-TWIN-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.