INDUSTRIAL COMPONENT DATA

# UISLKG 35 0443065 PHOENIX CONTACT Installation ground terminal block, Screw connection, Cross section: 0.75 ..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UISLKG 35**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UISLKG 35 |
| Catalog number | 0443065 |
| Category | Ground terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-8837EC9796 |
| Generated | 2026-11-18 |

## Product Overview

Installation ground terminal block, Screw connection, Cross section: 0.75 mm²
Ground terminal block for distribution, For connection sections of 35 mm² / AWG 2 an NS 32 copper rail must be inserted... o NS 35..., nominal voltage: 800 V, nominal current: 125 A, number of connections: 2, number of poles: 1, cross-section: 0.75 mm² - 35 mm², type of fixation: PE foot with fixing screw, M5, mounting class: NS 35/7.5, NS 35/15, NS 32, colour: yellow-green

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

General
Note Use an NS 32... or NS 35... copper DIN rail for connection cross sections of 35 mm²/2 AWG.
Number of levels 1
Number of connections 2
Nominal cross section 35 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
General
Rated surge voltage 8 kV
Overvoltage category III

Insulating material group I
Connection in acc. with standard IEC 60947-7-2
Open side panel nein
Number of positions 1
Dimensions
Width 15 mm
Length 55 mm
Height NS 35/7,5 51 mm
Height NS 35/15 58.5 mm
Height NS 32 56 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Conductor cross section solid min. 0.75 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section flexible min. 0.75 mm²
Conductor cross section flexible max. 35 mm²
Conductor cross section AWG min. 18
Conductor cross section AWG max. 2
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.75 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 35 mm²
2 conductors with same cross section, solid min. 0.75 mm²
2 conductors with same cross section, solid max. 16 mm²
2 conductors with same cross section, stranded min. 0.75 mm²
2 conductors with same cross section, stranded max. 10 mm²
2 conductors with same cross section, stranded, ferrules without pla...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UISLKG 35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.