INDUSTRIAL COMPONENT DATA

# USLKG 35 N 3074143 PHOENIX CONTACT Ground modular terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 35 N**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | USLKG 35 N |
| Catalog number | 3074143 |
| Category | Ground terminal block |
| Minimum order | 1 Pcs |
| Document ID | EO-75383048E0 |
| Generated | 2026-11-18 |

## Product Overview

Ground modular terminal block
Terminal block, number of connections: 2, connection type: Screw connection, Sizing cross-section: 35 mm², cross-section: 10 mm² - 35 mm², fixing type: PE foot with fixing screw, M5, mounting class: NS 35/7.5, NS 35/15, color: yellow-green

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3074143
Packing unit 50 pc
Catalog page Page 427 (C-1-2017)
GTIN 4046356347303
Weight per Piece (excluding packing) 79.400 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of levels 1
Number of connections 2
Nominal cross section 35 mm²
Color green-yellow

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 4.06 W
Open side panel No
Terminal block mounting 2.5 Nm ... 3 Nm (PE foot with mounting screw, M5)
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection Not guaranteed
Finger protection Not guaranteed
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f1= 5 Hz to f2= 150 Hz
ASD level 1.857 (m/s2)2/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 5 g
Shock duration 30 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 35 N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.