INDUSTRIAL COMPONENT DATA

USLKG 6 N 0442079 PHOENIX CONTACT Ground modular terminal block, Connection method: Screw connection, Number..

Brand: PHOENIX CONTACT | Manufacturer Part Number: USLKG 6 N



Manufacturer	PHOENIX CONTACT
MPN / Reference	USLKG 6 N
Catalog number	0442079
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-4027675710
Generated	2026-11-18

Product Overview

Ground modular terminal block, Connection method: Screw connection, Number of positions: 1, Cross section: 0.2 mm² Terminal block, number of connections: 2, connection type: Screw connection, cross-section: 0.2 mm² - 10 mm², fixing type: PE foot with fixing screw, M4, mounting class: NS 35/7.5, NS 35/15, NS 32, colour: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

General
Number of levels 1
Number of connections 2
Nominal cross section 6 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
General
Rated surge voltage 8 kV
Pollution degree 3
Overvoltage category III

Insulating material group I
Connection in acc. with standard IEC 60947-7-2
Open side panel nein
Number of positions 1
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Dimensions
Width 8.2 mm
Length 42.5 mm
Height 45.8 mm
Height NS 35/7,5 47 mm
Height NS 35/15 54.5 mm
Height NS 32 52 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-2
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 8
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / USLKG 6 N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.