INDUSTRIAL COMPONENT DATA

# GW EIP/MODBUS 1E/1DB9 1062540 PHOENIX CONTACT The GW EIP/MODBUS... enables two-way communication between Eth..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: GW EIP/MODBUS 1E/1DB9**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | GW EIP/MODBUS 1E/1DB9 |
| Catalog number | 1062540 |
| Category | PLC communication module |
| Minimum order | 1 Pcs |
| Document ID | EO-09E61D2230 |
| Generated | 2026-11-18 |

## Product Overview

The GW EIP/MODBUS... enables two-way communication between EtherNet/IP™ and Modbus protocols. Includes one RJ45 port and one D-SUB 9 port.
The GW EIP/MODBUS... allows two-way communication between EtherNet/IP™ and Modbus protocols. It comprises an RJ45 connection and a D-SUB-9 connection.

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Safety |

## Additional Product Information

Key Commercial Data
Orderkey 1062540
Packing unit 1 pc
GTIN 4055626718095
Weight per Piece (excluding packing) 180.000 g
Custom tariff number 85176200
Country of origin US (United States)
Drawings
Ambient conditions
Power supply

Function
Environmental Product Compliance
Dimensions
General
Serial interface
Standards and Regulations
Classifications
Drawings
Block diagram
Back to topDimensions
Width 22.5 mm
Height 99 mm
Depth 115 mm
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Permissible humidity (operation) 10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Altitude < 2000 m
Degree of protection IP20
Noise immunity EN 61000-6-2:2005
Back to topGeneral
Electrical isolation IEC UL 61010-1 (VCC // Ethernet)
Test voltage data interface/data interface 1.5 kVrms(50 Hz, 1 min.)
Test voltage data interface/power supply 1.5 kVrms
1.5 kVrms(50 Hz, 1 min.)
Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU
Noise emission EN 61000-6-4
Net weight 168.5 g
Housing material PA 6.6
Color gray
MTBF 92.1 Years (Telcordia standard, 25°C temperature, 50% stress, Environmental Factor = 1.0)
61.4 Years (Telcordia standard, 40°C temperature, 50% stress, Environmental Factor = 1.5)
Conformance CE-compliant
UL, USA UL 61010-1
UL, USA/Canada Class I, Div. 2, Groups A, B, C, D T4A
Back to topPower supply
Supply voltage range 10.8 V DC ... 30 V...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GW EIP/MODBUS 1E/1DB9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.