INDUSTRIAL COMPONENT DATA

SAC-5PH-M-F/2XF SH1 SCO 1417414 PHOENIX CONTACT H distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5PH-M-F/2XF SH1 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5PH-M-F/2XF SH1 SCO
Catalog number	1417414
Category	Sensor actuator adapter
Minimum order	1 Pcs
Document ID	EO-094D414776
Generated	2026-11-19

Product Overview

H distributor
H Distributor, 5-Pole, Shielded, M12 Straight Connector, Coding: A, A Straight Female M12, Coding: A and Straight Female M12, Coding: A, M12 Non-Rotating Thread, Parallel Purge Nozzle

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1417414
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 436 (C-2-2017)
GTIN 4046356525138
Weight per Piece (excluding packing) 60.000 g
Custom tariff number 85366990
Country of origin PL (Poland)
Dimensions
Center distance 21 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Color handle area black
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Characteristics head 2
Color black
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
Classifications
eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127061800eCl@ss 6.027279200eCl@ss 7.027279218eCl@ss 8.027279218eCl@ss 9.027440106
ETIM 4.0EC002061ETIM 5.0EC001855ETIM 6.0EC002925
UNSPSC 6.0131251501UNSPSC 7.090131251501UNSPSC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5PH-M-F/2XF SH1 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.