INDUSTRIAL COMPONENT DATA

HC-26P1NT24300 1615340 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-26P1NT24300



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-26P1NT24300
Catalog number	1615340
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-DB9222542F
Generated	2026-11-19

Product Overview

Device connector, rear mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1615340
Packing unit 12 pc
Note Made to Order (non-returnable)
GTIN 4046356439602
Weight per Piece (excluding packing) 52.700 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Type of locking Screw locking
Insertion/withdrawal cycles mechanical 50
Direction of rotation of contact chamber numbering Standard
Coding N
Contact connection method Solder-in connection
Type of contacts Pin

Number of positions 26
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Pg housing screw connection none
Mounting type 4x M3
Ambient conditions
Ambient temperature -20 °C ... 125 °C
Degree of protection IP67, when plugged in
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Contact material CuZn
Contact surface Nickel-plated, gold coating
Specifications according to DIN EN 61984:2001
Installation height max. 2000 m
Nominal / operating voltage of power contacts 150 V
Rated surge voltage of power contacts 1.5 kV
Overvoltage category of power contacts II
Degree of pollution of power contacts 3
Overvoltage category of signal contacts II
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.1272607xxeCl@ss 5.027260701eCl@ss 5.127260700e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-26P1NT24300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.