INDUSTRIAL COMPONENT DATA

HC-ADV-B24-1TM32-1SM25-EMC-PS 1423228 PHOENIX CONTACT Housing HC-ADV-B24-1TM32-1SM25-EMC-PS 1423228

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-ADV-B24-1TM32-1SM25-EMC-PS



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-ADV-B24-1TM32-1SM25-EMC-PS
Catalog number	1423228
Category	Housing for rectangular connectors
Minimum order	50 Pcs
Document ID	EO-B0C2C09B73
Generated	2026-11-19

Product Overview

Housing - HC-ADV-B24-1TM32-1SM25-EMC-PS - 1423228
B24 Aerial Housing, Screw Lock, Material: Die-cast Aluminum, Seawater Resistant, Cable Outlets: 2, Straight, Side, Height: 93.7 mm, Cable Gland: Without, Tubing: No, 1x M32 / 1x M25, Offshore/EMC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Sleeve housing B24, Screw locking, material: Die-cast aluminum, salt water resistant, cable outlets: 2, straight, lateral, height: 93.7 mm, cable gland: none, support sleeve: no, 1x M32 / 1x M25, Offshore/EMC
Key Commercial Data
Orderkey 1423228
Packing unit 1
GTIN 4055626327907
Custom tariff number 85389099
Dimensions
Height 93.7 mm
Width 57 mm
Length 152 mm

Length of the assembly cutout 112 mm
Width of the assembly cutout 35 mm
Ambient conditions
Degree of protection of housing (IP) IP66
IP68 (0.2 bar/24 h)
Degree of protection of housing (NEMA) 4 (NEMA 250)
4X (NEMA 250)
6P (NEMA 250)
12 (NEMA 250)
Ambient temperature (operation) -40 °C ... 125 °C
General
Note for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
Size B24
Housing type Sleeve housing
Locking type Screw locking
Torque 3 Nm (Locking screw)
Fixing screws M6 (screw head: Pozidrive)
No. of cable outlets 2
Cable outlet straight, lateral
Screw connection none
Type of the screw connection 1x M32 / 1x M25
Housing material Die-cast aluminum, salt water resistant
Housing surface material uncoated
Seal material NBR, conductive
Material of locking screw Stainless steel
Assembly instructions M6 locking screw, with Pozidrive head
Connection To ensure optimum shielding, any insulating power coating must be removed from the profile gasket area on the control cabinet panel. Tightening torque of locking screw: 3 Nm.
Classifications
eCl@ss
eCl@ss 5.1 27261200
eCl@ss 6.0 27261200
eCl@ss 7.0 27440202
eCl@ss 9.0 27440202
ETIM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-ADV-B24-1TM32-1SM25-EMC-PS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.