INDUSTRIAL COMPONENT DATA

# HC-B 16-KMQ-H-O1STM40 1414349 PHOENIX CONTACT HEAVYCON B16 coupling housing, with double locking latch, heig..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-KMQ-H-O1STM40**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | HC-B 16-KMQ-H-O1STM40 |
| Catalog number | 1414349 |
| Category | Housing for rectangular connectors |
| Minimum order | 10 Pcs |
| Document ID | EO-AB1C7E0DA0 |
| Generated | 2026-11-18 |

## Product Overview

HEAVYCON B16 coupling housing, with double locking latch, height: 82 mm, with 1 x M40 thread, straight cable outlet
HEAVYCON B16 coupling box, with cross flange, height 82 mm, with 1x M40 thread, straight cable outlet

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Key Commercial Data
Orderkey 1414349
Packing unit 1 pc
Minimum order quantity 10 pc
GTIN 4055626023885
Weight per Piece (excluding packing) 240.000 g
Custom tariff number 85389099
Country of origin DE (Germany)
Drawings
Ambient conditions
Environmental Product Compliance
Dimensions

General
Classifications
Drawings
Dimensional drawing
Dimensional drawing
Back to topDimensions
Height 82 mm
Back to topAmbient conditions
Degree of protection IP65
Ambient temperature (operation) -40 °C ... 125 °C
Back to topGeneral
Note For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K
Type B16
Degree of protection IP65
Locking type with double locking latch
Type of the screw connection 1x M40
Pg screw connection none
Cable outlet straight
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray
Seal material NBR
Ambient temperature (operation) -40 °C ... 125 °C
Back to topEnvironmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 10.0.1 27440202
eCl@ss 5.1 27261200
eCl@ss 6.0 27261200
eCl@ss 7.0 27440202
eCl@ss 8.0 27440202
eCl@ss 9.0 27440202
Back to topETIM
ETIM 5.0 EC000437
ETIM 6.0 EC000437
ETIM 7.0 EC000437
Back to topUNSPSC
UNSPSC 13.2 31261501
UNSPSC 18.0 31261501
UNSPSC 19.0 31261501
UNSPSC 20.0 31261501
UNSPSC 21.0 31261501
Back to top

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-KMQ-H-O1STM40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.