INDUSTRIAL COMPONENT DATA

# HC-BB10-I-PT-M 1014418 PHOENIX CONTACT Contact insert, number of positions: 10+PE, size: B6, power contacts:..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-BB10-I-PT-M**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | HC-BB10-I-PT-M |
| Catalog number | 1014418 |
| Category | Contact insert for rectangular connectors |
| Minimum order | 1 Pcs |
| Document ID | EO-2DDA66EF52 |
| Generated | 2026-11-19 |

## Product Overview

Contact insert, number of positions: 10+PE, size: B6, power contacts: 10, control contacts: 0, number of connections per position: 1, Pin, Push-in connection, 500 V, 16 A, 0.5 mm² ... 2.5 mm², application: Power

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Key Commercial Data
Orderkey 1014418
Packing unit 1 pc
Catalog page Page 553 (C-2-2019)
GTIN 4055626494418
Weight per Piece (excluding packing) 60.000 g
Custom tariff number 85366990
Country of origin CN (China)
Drawings
Ambient conditions
Electrical characteristics
Environmental Product Compliance
General
Material data

Standards and Regulations
Classifications
Drawings
Dimensional drawing
Mounting cutout when used without housing
Back to topGeneral
Note Connectors may be operated only when there is no load/voltage.
Connection method Push-in connection
Number of connections per position 1
Degree of pollution 3
Overvoltage category III
Number of positions 10+PE
No. of power contacts 10
No. of control contacts 0
Insertion/withdrawal cycles >= 500
Size B6
Contact numbering 1 - 10
Conductor cross section 0.5 mm² ... 2.5 mm² (with ferrule)
Connection cross section AWG 20 ... 14 (with ferrule)
Stripping length of the individual wire 10 mm
Minimum housing height 72 mm
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 125 °C (including heating up of contacts)
Back to topMaterial data
Contact material Copper alloy
Contact surface material Ag
Contact carrier material PC
Back to topElectrical characteristics
Rated voltage (III/3) 500 V
Rated surge voltage 6 kV
Rated current 16 A (power contacts)
Back to topStandards and Regulations
Flammability rating ac...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-BB10-I-PT-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.