INDUSTRIAL COMPONENT DATA

# HC-COM-BAWS-EL-AL 1078593 PHOENIX CONTACT Panel mounting base COM, with single locking latch, material: Die-..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-BAWS-EL-AL**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | HC-COM-BAWS-EL-AL |
| Catalog number | 1078593 |
| Category | Housing for rectangular connectors |
| Minimum order | 1 Pcs |
| Document ID | EO-B116B8C915 |
| Generated | 2026-11-18 |

## Product Overview

Panel mounting base COM, with single locking latch, material: Die-cast aluminum, salt water resistant, height: 41.7 mm, cable gland: none, support sleeve: no, Standard
COM recessed housing, with longitudinal flange, material: Die-cast aluminium, seawater resistant, height: 37.5 mm, cable gland: without, Standard

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Key Commercial Data
Orderkey 1078593
Packing unit 1 pc
Catalog page Page 653 (C-2-2019)
GTIN 4055626794112
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85389099
Country of origin CN (China)
Drawings
Ambient conditions
Standards and Regulations
Dimensions

General
Classifications
Drawings
Dimensional drawing
Back to topDimensions
Height 41.7 mm
Width 64.5 mm
Length 46.6 mm
Back to topAmbient conditions
Degree of protection (IP) IP66
Ambient temperature (operation) -40 °C ... 125 °C
Back to topGeneral
Size COM
Housing type Panel mounting base
Color gray aluminum
Locking type with single locking latch
Screw connection none
Housing material Die-cast aluminum, salt water resistant
Seal material NBR
Material lock PA
Flammability rating according to UL 94 V0
Back to topStandards and Regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 10.0.1 27440202
eCl@ss 4.0 27140816
eCl@ss 4.1 27140816
eCl@ss 5.0 27143424
eCl@ss 5.1 27261200
eCl@ss 6.0 27261200
eCl@ss 7.0 27440202
eCl@ss 8.0 27440202
eCl@ss 9.0 27440202
Back to topETIM
ETIM 4.0 EC000437
ETIM 5.0 EC000437
ETIM 6.0 EC000437
ETIM 7.0 EC000437
Back to topUNSPSC
UNSPSC 6.01 31261502
UNSPSC 7.0901 31261502
UNSPSC 11 31261502
UNSPSC 12.01 31261502
UNSPSC 13.2 31261501
UNSPSC 18.0 31261501
UNSPSC 19.0 31261501

UNSPSC 20.0 31261501
UNSPSC 21.0 31261501
Back to top

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-BAWS-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.