INDUSTRIAL COMPONENT DATA

HC-COM-HHFS-1TTM25-EL-AL 1078590 PHOENIX CONTACT Sleeve housing COM, for single locking latch, material: Die..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-HHFS-1TTM25-EL-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-COM-HHFS-1TTM25-EL-AL
Catalog number	1078590
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-BF76553FBD
Generated	2026-11-19

Product Overview

Sleeve housing COM, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, height: 68 mm, cable gland: none, support sleeve: no, 1x M25, Standard
COM aerial housing, for longitudinal flange, material: Die-cast aluminum, seawater resistant, cable outlets: 1, straight, 1x M25, height: 68 mm, cable gland: without, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1078590
Packing unit 1 pc
Catalog page Page 653 (C-2-2019)
GTIN 4055626791890
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85389099
Country of origin CN (China)
Drawings
Ambient conditions
Standards and Regulations
Dimensions

General
Classifications
Drawings
Dimensional drawing
Back to topDimensions
Height 68 mm
Width 39 mm
Length 48.8 mm
Back to topAmbient conditions
Degree of protection (IP) IP66
Ambient temperature (operation) -40 °C ... 125 °C
Back to topGeneral
Size COM
Housing type Sleeve housing
Color gray aluminum
Locking type for single locking latch
No. of cable outlets 1
Cable outlet straight
Screw connection none
Type of the screw connection 1x M25
Housing material Die-cast aluminum, salt water resistant
Flammability rating according to UL 94 V0
Back to topStandards and Regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 10.0.1 27440202
eCl@ss 4.0 27140816
eCl@ss 4.1 27140816
eCl@ss 5.0 27143424
eCl@ss 5.1 27261200
eCl@ss 6.0 27261200
eCl@ss 7.0 27440202
eCl@ss 8.0 27440202
eCl@ss 9.0 27440202
Back to topETIM
ETIM 4.0 EC000437
ETIM 5.0 EC000437
ETIM 6.0 EC000437
ETIM 7.0 EC000437
Back to topUNSPSC
UNSPSC 6.01 31261502
UNSPSC 7.0901 31261502
UNSPSC 11 31261502
UNSPSC 12.01 31261502
UNSPSC 13.2 31261501
UNSPSC 18.0 31261501

UNSPSC 19.0 31261501
UNSPSC 20.0 31261501
UNSPSC 21.0 31261501
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-HHFS-1TTM25-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.