INDUSTRIAL COMPONENT DATA

HC-COM-SHOWS-1SGM25-PL-BK 1079393 PHOENIX CONTACT Box mounting bases COM, with single locking latch, materia..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-SHOWS-1SGM25-PL-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-COM-SHOWS-1SGM25-PL-BK
Catalog number	1079393
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-0EE309FBA6
Generated	2026-11-18

Product Overview

Box mounting bases COM, with single locking latch, material: PA, cable outlets: 1, lateral, height: 68 mm, cable gland: with, support sleeve: no, 1x M25, Standard
COM socket housing, with longitudinal flange, material: PA, cable outlets: 1, side, 1x M25, height: 36 mm, cable gland: with, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1079393
Packing unit 1 pc
Catalog page Page 652 (C-2-2019)
GTIN 4055626798493
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85389099
Country of origin CN (China)
Drawings
Ambient conditions

Standards and Regulations
Classifications
Dimensions
General
Environmental Product Compliance
Drawings
Dimensional drawing
Back to topDimensions
Height 68 mm
Wrench size, union nut 27 mm
External cable diameter 10 mm ... 16 mm
Back to topAmbient conditions
Degree of protection (IP) IP66
Ambient temperature (operation) -40 °C ... 125 °C
Back to topGeneral
Size COM
Housing type Box mounting bases
Color black
Locking type with single locking latch
No. of cable outlets 1
Cable outlet lateral
Screw connection with
Type of the screw connection 1x M25
Housing material PA
Seal material NBR
Material lock PA
Flammability rating according to UL 94 V0
Back to topStandards and Regulations
Flammability rating according to UL 94 V0
Back to topEnvironmental Product Compliance
REACh SVHC Lead 7439-92-1
Back to topClassifications
eCl@ss
eCl@ss 10.0.1 27440202
eCl@ss 4.0 27140816
eCl@ss 4.1 27140816
eCl@ss 5.0 27143424
eCl@ss 5.1 27261200
eCl@ss 6.0 27261200
eCl@ss 7.0 27440202
eCl@ss 8.0 27440202
eCl@ss 9.0 27440202
Back to topETIM
ETIM 4.0 EC000437
ETIM 5.0 EC000437
ETIM 6.0 EC000437
ETIM 7.0 EC000437

Back to topUNSPSC
UNSPSC 6.01 31261502
UNSPSC 7.0901 31261502
UNSPSC 11 31261502
UNSPSC 12.01 31261502
UNSPSC 13.2 31261501
UNSPSC 18.0 31261501
UNSPSC 19.0 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-SHOWS-1SGM25-PL-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.