INDUSTRIAL COMPONENT DATA

HC-EVO-B10-SHWSC-2SSM25-PLRBK 1421301 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-EVO-B10-SHWSC-2SSM25-PLRBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-EVO-B10-SHWSC-2SSM25-PLRBK
Catalog number	1421301
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-BACB0F290D
Generated	2026-11-18

Product Overview

Housing
B10 socket housing, with longitudinal flange, material: PA, protective cap material: PC, cable outlets: 2, side, 2x M25, height: 74 mm, cable gland: without, protective cover: yes, Standard, including 2x reduction adapters
B10 plinth case, with lock. longitudinal, material: PA 6.6-FR, cover material: PC, cable outlets: 2, lateral, 2x M25, height: 74 mm, screw connection for cable: without, protective cover: yes, Standard, incl. 2 reduction adapters

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1421301
Packing unit 1 pc
Catalog page Page 594 (C-2-2017)
GTIN 4055626264813
Weight per Piece (excluding packing) 194.000 g
Custom tariff number 85389099
Country of origin PL (Poland)
Dimensions
Height 74 mm
Width 57 mm

Length 93 mm
Ambient conditions
Degree of protection of housing (IP) IP66 (when plugged in or with locked protective cover)
Degree of protection of housing (NEMA) 12 (UL 50e)
Ambient temperature (operation) -40 °C ... 125 °C
General
Note For contact inserts HC-B10, BB18, DD42, M, K8/24, HV03-I-PT, HC- 3-E...C
Size B10
Housing type Box mounting bases
Color black
Locking type with single locking latch
No. of cable outlets 2
Cable outlet lateral
Screw connection none
Type of the screw connection 2x M25
Protective cover yes
Housing material PA
Seal material NBR
Material lock PA
Material, protective cover PA
Flammability rating according to UL 94 V0
Assembly instructions Two plastic reductions M32 to M25 are provided
Connection One of the two openings for the screw connections is sealed but can be broken open using a screwdriver.
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 13.231261501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-EVO-B10-SHWSC-2SSM25-PLRBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.