INDUSTRIAL COMPONENT DATA

HC-M-01-COAX-CK1,6-75-F 1066961 PHOENIX CONTACT Connector HC-M-01-COAX-CK1,6-75-F 1066961

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-01-COAX-CK1,6-75-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-01-COAX-CK1,6-75-F
Catalog number	1066961
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-6D430E8CFA
Generated	2026-11-19

Product Overview

Connector - HC-M-01-COAX-CK1,6-75-F - 1066961
Connector, number of poles: 1, power contacts: 0, control contacts: 1, Female, Crimped connection, 48 V, 10 A, 0.14 mm² ... 2.5 mm², outer diameter of the cable:3 mm ... 9.5 mm, application: COAX, 75 ?

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Connector, power contacts: 0, control contacts: 1, Socket, 50 V, 10 A, 0.14 mm² ... 2.5 mm², external cable diameter:3 mm ... 9.5 mm, 75 Ohm
Key Commercial Data
Orderkey 1066961
Packing unit 1
GTIN 4055626733876
Custom tariff number 85366990
General
Note Order crimp contacts separately
The potential of the EMC connector housing is isolated from the potential of the heavy connector.
Clamps for the clamping range of 3 mm - 6 mm and 6 mm - 9.5 mm
Can be used in Order No.: 1417376 HC-M-02-EMC-F
For 75 ? coaxial cables

Degree of pollution 3
Overvoltage category III
No. of power contacts 0
No. of control contacts 1
Insertion/withdrawal cycles >= 500
Conductor cross section 0.14 mm² ... 2.5 mm²
Connection cross section AWG 26 ... 14
Stripping length of the individual wire 8 mm
Minimum external conductor diameter 3 mm
Maximum external conductor diameter 9.5 mm
Assembly instructions Disassemble the contact with tool, order no.: 1884869
Connection Sheath stripping length: 23 mm, shield length: 13 mm, inner conductor stripping length: 8 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Material data
Contact material Copper alloy
Contact surface material AU
Contact carrier material PC
Electrical characteristics
Rated voltage (III/3) 50 V
Rated surge voltage 0.8 kV
Rated current 10 A
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-01-COAX-CK1,6-75-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.